


F U N I I N O X  
S T A I N L E S S S T E E L  
W I R E R O P E

italmet

**Fune 1x9 spiroidale**  
Wire rope 1x9 spiral



**19 FILI**


crociata destra  
crociata sinistra

**19 WIRES**

right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
1,50	0,30	1,20	1,89	0,19
1,80	0,35	1,60	2,61	0,26
2,00	0,40	2,00	3,34	0,34
2,50	0,50	3,10	5,27	0,53
3,00	0,60	4,50	7,56	0,77
3,50	0,70	6,10	10,27	1,04
4,00	0,80	8,00	13,38	1,36
5,00	1,00	12,51	20,84	2,12
6,00	1,20	17,85	30,10	3,06
7,00	1,40	24,25	40,89	4,16
8,00	1,60	31,70	53,32	5,43
10,00	2,00	49,55	78,07	7,95
12,00	2,40	71,30	112,47	11,46
14,00	2,80	97,10	142,43	14,51
16,00	3,20	127,00	181,00	18,45

**Fune 7x7 anima metallica**  
Wire rope 7x7 WSC



**49 FILI**


crociata destra  
crociata sinistra

**49 WIRES**

right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
1,50	0,16	0,90	1,58	0,16
1,80	0,19	1,20	2,20	0,22
2,00	0,22	1,71	2,92	0,29
2,50	0,27	2,50	4,36	0,44
3,00	0,31	3,54	5,35	0,54
3,50	0,37	4,80	7,46	0,76
4,00	0,43	6,30	9,97	1,01
5,00	0,53	9,85	15,06	1,59
6,00	0,65	14,20	22,40	2,28
7,00	0,75	19,30	30,27	3,08
8,00	0,84	25,20	38,59	3,93

**Fune 6x19 anima tessile**  
Wire rope 6x19 FC




**114 FILI**  
crociata destra  
crociata sinistra

**114 WIRES**  
right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
3,00	0,19	3,00	5,01	0,51
4,00	0,25	5,30	7,73	0,78
5,00	0,31	8,20	11,88	1,21
6,00	0,37	11,50	16,97	1,72
7,00	0,45	17,00	24,78	2,52
8,00	0,50	21,00	30,92	3,15
10,00	0,63	32,50	48,57	4,95

**Fune 7x19 anima metallica**  
Wire rope 7x19 WSC




**133 FILI**  
crociata destra  
crociata sinistra

**133 WIRES**  
right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
2,00	0,13	1,60	2,67	0,27
2,50	0,16	2,40	4,10	0,41
3,00	0,19	3,42	5,71	0,58
3,50	0,22	4,70	7,70	0,78
4,00	0,25	6,09	8,92	0,90
5,00	0,31	9,52	13,69	1,39
6,00	0,37	13,80	19,64	2,00
6,50	0,40	16,00	22,94	2,33
7,00	0,45	18,70	28,21	2,87
8,00	0,50	24,40	35,67	3,63
9,00	0,55	30,80	45,61	4,64
9,50	0,60	34,50	50,23	5,12
10,00	0,63	38,10	55,93	5,70
12,00	0,75	54,80	76,11	7,75
14,00	0,90	74,60	108,67	11,07
16,00	1,00	97,40	136,43	13,90

**Fune 6x36 WS AM anima metallica**  
Wire rope 6x36 WS IWRC




**216 FILI**  
crociata destra  
crociata sinistra

**216 WIRES**  
right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
8,00	0,43	26,80	36,37	3,70
10,00	0,55	40,00	57,38	5,84
12,00	0,65	57,00	81,21	8,27
14,00	0,75	80,00	110,54	11,26
16,00	0,90	105,00	150,38	15,32
18,00	1,00	135,00	187,08	19,07
20,00	1,10	167,00	229,69	23,41

**Fune 18x7 ANTIGIRO anima metallica**  
Wire rope 18x7 WSC NOT ROTATING



**126 FILI**  
crociata destra  
crociata sinistra

**126 WIRES**  
right regular lay  
left regular lay

Ø fune Ø rope	Ø fili esterni Ø outer wires	peso per mt weight for meter	carico rottura min. MBL	
			kn	ton
4,00	0,25	6,43	8,70	0,88
5,00	0,31	10,00	13,28	1,40
6,00	0,37	14,50	18,99	1,93
6,50	0,40	16,40	22,27	2,27
7,00	0,43	19,70	26,07	2,65
8,00	0,50	25,70	34,18	3,48
10,00	0,63	40,20	53,71	5,47
12,00	0,75	57,90	77,61	7,91
14,00	0,87	78,80	104,19	10,62



**ITALMET SRL**

VIA DELLE INDUSTRIE, 81 - 48122 RAVENNA - ITALY

PH. + 39 0544 451555 FAX + 39 0544 451345

INFO@ITALMET.COM WWW.ITALMET.COM